

DOMINION SURE SEAL LTD  
6175 DANVILLE ROAD  
MISSISSAUGA; L5T 2H7; ONTARIO

**PRODUCT: SLAP PIT BULL ADHESION PROMOTER 500G / 17.64OZ****Section 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

SUPPLIER ..... DOMINION SURE SEAL LTD  
6175 DANVILLE ROAD  
ONTARIO  
CANADA  
L5T 2H7  
CANUTEC EMERGENCY #: 1-613-996-6666(24HR)  
PRODUCT NAME ..... SLAP PIT BULL ADHESION PROMOTER 500G / 17.64OZ  
CHEMICAL FAMILY ..... ADHESION PROMOTER.  
MOLECULAR WEIGHT ..... NOT APPLICABLE.  
CHEMICAL FORMULA ..... MIXTURE.  
TRADE NAMES & SYNONYMS ..... SLAP PIT BULL ADHESION PROMOTER 500G / 17.64OZ  
PRODUCT USES ..... PRIMER.  
CAS # ..... NOT APPLICABLE.

**Section 02: COMPOSITION/INFORMATION INGREDIENTS**

Hazardous Ingredients	%	Exposure Limit	C.A.S.#	LD/50, Route,Species	LC/50 Route,Species
TOLUENE	10-30	50 ppm	108-88-3	5000 mg/kg ORAL - RAT	8000 ppm (4 hr) INHAL - RAT
ACETONE	15-40	750 ppm	67-64-1	>9750 mg/kg ORAL - RAT	>16,000 ppm (4 hr) INHAL - RAT
ETHYL BENZENE	1- 5	100 ppm	100-41-4	5460 mg/kg ORAL-RAT	NOT AVAILABLE
ISOPROPANOL	1-5	400 ppm	67-63-0	>4720 mg/kg ORAL - RAT	12000 ppm (8hr) INHAL - RAT
METHYL ETHYL KETONE	5-10	200 ppm	78-93-3	3400 mg/kg ORAL - RAT	8000 ppm (8 hr) INHAL - RAT
ISOBUTANE	7-13	1000 ppm	75-28-5	NOT APPLICABLE	142,500 ppm (4h) INHAL - RAT
PROPANE	10-30	1000 ppm	74-98-6	NOT APPLICABLE	NOT AVAILABLE

**Section 03: HAZARDS IDENTIFICATION**

ROUTE OF ENTRY:  
 INGESTION ..... MAY CAUSE HEADACHE, NAUSEA, VOMITING AND WEAKNESS.  
 INHALATION ..... INHALATION OF SOLVENTS MAY CAUSE IRRITATION. PROPELLANT IS A SIMPLE ASPHYXIANT.  
 EYE CONTACT ..... MAY CAUSE IRRITATION.  
 SKIN ABSORPTION ..... NO DATA AVAILABLE FOR THIS PRODUCT MIXTURE.  
 SKIN CONTACT ..... MAY CAUSE IRRITATION.  
 EFFECTS OF ACUTE EXPOSURE ..... DIZZINESS, NAUSEA. IRRITATION TO SKIN & EYES.  
 EFFECTS OF CHRONIC EXPOSURE ..... LONG TERM EXPOSURE (YEARS) TO HIGH CONCENTRATIONS OF VAPOR MAY CAUSE LUNG, LIVER OR KIDNEY DAMAGE. THE SOLVENTS LISTED HAVE BEEN REPORTED TO AFFECT THE CENTRAL NERVOUS SYSTEM. ASPIRATION HAZARD IF SWALLOWED. EYE AND SKIN IRRITANT. MAY IRRITATE RESPIRATORY TRACT. DELIBERATELY CONCENTRATING AND INHALING THE VAPOR OF THE CONTENTS MAY BE HARMFUL OR FATAL.  
 EXPOSURE LIMIT OF MATERIAL ..... SEE SECTION 2.

**Section 04: FIRST AID MEASURES**

EMERGENCY FIRST AID PROCEDURE ..... IN CASE OF EYE CONTACT, FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION. FOR SKIN, WASH THOROUGHLY WITH SOAP AND WATER. IF AFFECTED BY INHALATION OF VAPOUR OR SPRAY MIST, REMOVE TO FRESH AIR. IF SWALLOWED; DO NOT INDUCE VOMITING, GET MEDICAL ATTENTION.

**Section 05: FIRE FIGHTING MEASURES**

AUTO IGNITION TEMPERATURE (°C) ..... 399-514.  
 SPECIAL PROCEDURES ..... WATER FROM FOGGING NOZZLES MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT BUILD-UP IF EXPOSED TO EXTREME TEMPERATURES. FULL PROTECTIVE EQUIPMENT INCLUDING SELF CONTAINED BREATHING APPARTATUS SHOULD BE WORN IN A FIRE INVOLVING THIS MATERIAL.  
 FLAMMABILITY ..... EXTREMELY FLAMMABLE.  
 IF YES, UNDER WHICH CONDITIONS? ..... EXCESSIVE HEAT, SPARKS AND OPEN FLAME.  
 EXTINGUISHING MEDIA ..... WATER, CARBON DIOXIDE, DRY CHEMICAL, FOAM.  
 FLASH POINT (C), TAG CLOSED CUP ..... LOWEST KNOWN VALUE IS ACETONE @ -18C.  
 UPPER FLAMMABLE LIMIT ..... 12.8.  
 (% BY VOLUME)

**PRODUCT: SLAP PIT BULL ADHESION PROMOTER 500G / 17.64OZ****Section 05: FIRE FIGHTING MEASURES**

LOWER FLAMMABLE LIMIT..... 1.1.  
 (% BY VOLUME)  
 EXPLOSION DATA  
 SENSITIVITY TO STATIC DISCHARGE..... NOT APPLICABLE.  
 SENSITIVITY TO IMPACT..... NOT APPLICABLE.  
 HAZARDOUS COMBUSTION  
 PRODUCTS..... HYDROCARBON FUMES AND SMOKE. CARBON MONOXIDE WHERE COMBUSTION IS  
 INCOMPLETE.  
 AEROSOL FLAME PROJECTION  
 CLASSIFIED AS:..... >45cm.  
 FLASHBACK..... NONE.

**Section 06: ACCIDENTAL RELEASE MEASURES**

LEAK/SPILL..... REMOVE ALL SOURCES OF IGNITION. USE AN INERT ABSORBENT MATERIAL, AND  
 NON-SPARKING TOOLS. VENTILATE AREA. PREVENT FROM ENTERING A WATERCOURSE.

**Section 07: HANDLING AND STORAGE**

STORAGE NEEDS..... KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAMES.  
 ENGINEERING CONTROLS..... VENTILATION - LOCAL (MECHANICAL IF USED INDOORS ON A CONTINUOUS BASIS).  
 HANDLING PROCEDURES AND EQUIPMENT..... STORE IN A COOL, WELL VENTILATED AREA NOT TO EXCEED 50 DEG C.  
 SYNERGISTIC MATERIALS..... NONE KNOWN.

**Section 08: EXPOSURE CONTROLS/PERSONAL PROTECTION**

GLOVES/ TYPE..... WEAR CHEMICAL RESISTANT GLOVES.  
 RESPIRATORY/TYPE..... IF USED INDOORS ON A CONTINUOUS BASIS, USE OF A CARTRIDGE TYPE RESPIRATOR  
 (NIOSH/MSHATC 23C OR EQUIVALENT) IS RECOMMENDED.  
 EYE/TYPE..... SAFETY GLASSES.  
 FOOTWEAR/TYPE..... NOT NORMALLY REQUIRED.  
 OTHER/TYPE..... NOT REQUIRED.

**Section 09: PHYSICAL AND CHEMICAL PROPERTIES**

PHYSICAL STATE..... AEROSOL.  
 APPEARANCE..... DARK GREEN.  
 ODOR..... PUNGENT.  
 ODOR THRESHOLD..... NOT AVAILABLE.  
 VAPOUR PRESSURE(PSIG)-AEROSOL..... 50-60.  
 @ 20 C  
 BOILING POINT (°C)(CONC)..... 56 - 111.  
 EVAPORATION RATE..... GREATER THAN 1.  
 n-BUTYL ACETATE = 1  
 VAPOUR DENSITY (AIR=1)..... GREATER THAN 1.  
 (BY WEIGHT)  
 SOLUBILITY IN WATER g/L (20°C)..... NOT AVAILABLE.  
 pH..... NOT APPLICABLE.  
 SPECIFIC GRAVITY (LIQUID)..... 0.83-0.87.  
 COEFFICIENT OF WATER/OIL DIST..... NOT AVAILABLE.  
 FREEZING POINT: (°C)..... NOT AVAILABLE.  
 AEROSOL PERCENT VOLATILE..... 91-92.  
 (BY WEIGHT).

**Section 10: STABILITY AND REACTIVITY**

HAZARDOUS PRODUCTS OF  
 DECOMPOSITION..... HYDROCARBON FUMES AND SMOKE. CARBON MONOXIDE WHERE COMBUSTION IS  
 INCOMPLETE.  
 CHEMICAL STABILITY:  
 YES..... UNDER NORMAL CONDITIONS.  
 NO, WHICH CONDITIONS?..... NOT APPLICABLE.  
 COMPATIBILITY WITH OTHER SUBSTANCES:  
 NO, WHICH ONES?..... STRONG OXIDIZING AGENTS.  
 REACTIVITY CONDITIONS?..... NOT APPLICABLE.  
 HAZARDOUS POLYMERIZATION..... WILL NOT OCCUR.

**Section 11: TOXICOLOGICAL INFORMATION**

REPRODUCTIVE EFFECTS..... TOLUENE - PROLONGED AND REPEATED EXPOSURE OF PREGNANT ANIMALS TO TOLUENE  
 (LEVELS GREATER THAN APPROXIMATELY 1500 ppm) HAS BEEN REPORTED TO CAUSE  
 ADVERSE FETAL DEVELOPMENTAL EFFECTS.  
 CARCINOGENICITY OF MATERIAL..... ETHYL BENZENE: DESIGNATED AS IARC GROUP 2B CARCINOGEN-POSSIBLY CARINOGENIC  
 TO HUMANS.  
 MUTAGENICITY..... NO INFORMATION IS AVAILABLE AND NO ADVERSE MUTAGENIC EFFECTS ARE  
 ANTICIPATED.  
 IRRITANCY OF MATERIAL..... SKIN/EYE IRRITANT. METHYL ETHYL KETONE MAY CAUSE EMBRYOTOXIC EFFECTS IN  
 LABORATORY ANIMALS.  
 SENSITIZING CAPABILITY OF MATERIAL..... UNKNOWN.  
 TERATOGENICITY..... NO INFORMATION IS AVAILABLE AND NO ADVERSE TERATOGENIC EFFECTS ARE  
 ANTICIPATED.

**PRODUCT: SLAP PIT BULL ADHESION PROMOTER 500G / 17.64OZ****Section 12: ECOLOGICAL CONSIDERATIONS**

ENVIRONMENTAL..... NOT AVAILABLE.

**Section 13: DISPOSAL CONSIDERATIONS**

WASTE DISPOSAL..... DO NOT PUNCTURE OR INCINERATE CONTAINERS, EVEN WHEN EMPTY. DISPOSE OF IN ACCORDANCE WITH LOCAL, PROVINCIAL AND FEDERAL REGULATIONS.

**Section 14: TRANSPORTATION INFORMATION**D.O.T. CLASSIFICATION..... CONSUMER COMMODITY, ORM-D.  
T.D.G. CLASSIFICATION..... CONSUMER COMMODITY (AEROSOLS, UN1950, CLASS 2.1).**Section 15: REGULATORY INFORMATION**

## CANADIAN REGULATIONS:

WHMIS CLASSIFICATION..... A,B5,D2A,D2B.  
CNFC SECTION 3.3.5..... LEVEL 3.  
CEPA (Canadian Environmental Protection Act) ALL SUBSTANCES IN THIS PRODUCT ARE LISTED ON THE CANADIAN DOMESTIC SUBSTANCES LIST (DSL) OR ARE NOT REQUIRED TO BE LISTED.

## U.S. REGULATIONS:

HMIS RATING HEALTH..... 2 MODERATE HAZARD.  
HMIS RATING FLAMMABILITY..... 4 SEVERE HAZARD.  
HMIS RATING REACTIVITY..... 0 MINIMAL HAZARD.  
NFPA CODE 30B..... LEVEL 3.  
SARA 313 INFORMATION:..... THIS PRODUCT CONTAINS THE FOLLOWING SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372:CAS #: CHEMICAL NAME:  
\*108-88-3 TOLUENE  
\*100-41-4 ETHYL BENZENE  
\*108-10-1 METHYL ISOBUTYL KETONE

CALIFORNIA PROPOSITION 65:..... THE FOLLOWING STATEMENT IS MADE IN ORDER TO COMPLY WITH THE CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986:

WARNING: THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM.

CAS #: CHEMICAL NAME:  
\*108-88-3 TOLUENE  
\*100-41-4 ETHYL BENZENE

TSCA (Toxic Substances Control Act)..... ALL COMPONENT OF THIS PRODUCT ARE LISTED ON THE TSCA INVENTORY. ANY IMPURITIES PRESENT IN THIS PRODUCT ARE EXEMPT FROM LISTING.

VOC (w/w%)..... 52-53.

V.O.C.(M.I.R.)..... N/A.

**Section 16: OTHER INFORMATION**

NOTICE FROM DOMINION SURE SEAL LTD ..... THE INFORMATION ON THIS MATERIAL SAFETY DATA SHEET IS PROVIDED BY DOMINION SURE SEAL LTD FREE OF CHARGE. WHILE BELIEVED TO BE RELIABLE, IT IS INTENDED FOR USE BY SKILLED PERSONS AT THEIR OWN RISK. DOMINION SURE SEAL LTD. ASSUMES NO RESPONSIBILITY FOR EVENTS RESULTING OR DAMAGES INCURRED FROM ITS USE. THE INFORMATION ON THIS MATERIAL SAFETY DATA SHEET RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED HEREIN AND DOES NOT RELATE TO USE IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY PROCESS.

PREPARED BY..... TECHNICAL SERVICES  
PREPARATION DATE ..... June 1, 2010