

Material Safety Data Sheet

WHMIS 	Protective Clothing 	TDG Road / Rail
--	--	-----------------

Section 1. Product Identification and Uses

Product Name	TRIM ADHESIVE (STT)	CI#	Not applicable.
Synonyms	Not available.	DSL	Not available.
Chemical Name	Not applicable.	CAS #	Not applicable.
Chemical Formula	Chemical mixture.	Code	STT
Chemical Family	Various Hydrocarbons.	Molecular Weight	Not applicable.
Supplier	Dominion Sure Seal Ltd. 6175 Danville Road, Mississauga, Ontario L5T 2H7 PHONE: (905) 670-5411	Manufacturer	Manufactured for: Dominion Sure Seal Ltd.
Material Uses	Trim adhesive.		



Section 2. Hazardous Ingredients

Name	CAS #	% by Weight	LC ₅₀ /LD ₅₀
1) Methylene chloride	75-09-2	40-70	ORAL (LD50) mg/kg: Acute: 1987 (Mouse). 2388 (Rat). 4368 (Rat).
2) Toluene	108-88-3	5-10	ORAL (LD50) mg/kg: Acute: 6520 (Rat). 2600 (Rat). DERMAL (LD50) mg/kg: Acute: 12210 (Rabbit). VAPOR (LC50) ppm : Acute: 8000 (Rat) (4 hour(s)).
3) Liquefied petroleum gas	68476-85-7	10-30	Not available.

Section 3. Physical Data

Physical State and Appearance	Liquid (Aerosol Concentrate).	Odor	Mild ethereal.
pH (1% Soln/Water)	Not available.	Taste	Not available.
Odor Threshold	214 ppm based on data for: Methylene chloride. Weighted average: 193 ppm	Color	Light straw.
Volatility	Not available.		
Evaporation Rate	14.5 based on data for: Methylene chloride. Weighted average: 13.27 [Butyl acetate.]		
Melting Point	Not available.		
Boiling Point	39.75°C (103.5°F) based on data for: Methylene chloride. Weighted average: 46.63°C (115.9°F)		
Density	1.15-1.22 (Water = 1)		
Vapor Density	Weighted average: 2.95 (Air = 1)		
Vapor Pressure	Weighted average: 317.01 mm of Hg (@ 20°C)		
LogK_{ow}	Not available.		
Ionicity (Surface Active Agent)	Not available.		
Critical Temperature	Not available.		
Instability Temperature	Not available.		
Conditions of Instability	No additional remark.		
Dispersion Properties	See solubility in water.		
Solubility	Insoluble in water.		

Continued on Next Page



WHMIS	Protective Clothing	TDG Road / Rail
		
A B-5 D-1B		CONSUMER COMMODITY.

Section 4. Fire and Explosion Data

The Product is:	Extremely Flammable Aerosol
Auto-ignition Temperature	480°C (896°F) based on data for: Toluene.
Products of Combustion	These products are carbon oxides (CO, CO ₂), hydrogen chloride, phosgene and other irritating gases.
Flash Points	CLOSED CUP: (Setaflash) 4.4°C (39.9°F) (Toluene).
Flammable Limits	LOWER: 1% UPPER: 19%
Extinguishing Media	SMALL FIRE: Use DRY chemicals, carbon dioxide or foam. LARGE FIRE: Use foam or water fog. Cool containing vessels with water spray in order to prevent pressure build-up, autoignition or explosion. Avoid spreading burning liquid with water used to cool containers. Self-contained respiratory protection should be provided for firefighters.
Flammability	The flammability of an aerosol by WHMIS definition is determined by its flame-extension or its flashback. The flame-extension of this product is greater than 45 cm. FIRE CODE: Level 1 Aerosol (as per NFPA 30B). Do not use in the presence of open flame or spark. Do not place in hot water or near radiators, stoves or other sources of heat.
Risks of Explosion	Risk of explosion of the product in presence of mechanical impact: Do not subject aerosol cans to impact. Risk of explosion of the product in the presence of static discharge: Aerosol spray may be sensitive to static discharge due to flammable concentrate and flammable propellant. Vapours of this product may form a flammable/explosive mixture with air in enclosed areas when vapours present are between the lower (1.0%) and upper (19.0%) flammable limits and come into contact with open flames, sparks or static discharge. Do NOT expose aerosol containers to open flames, heat or ignition sources. Container may explode if heated.

Section 5. Reactivity

Stability	The product is stable.
Hazardous Decomposition Products	These products are carbon oxides (CO, CO ₂), sulphur oxides (SO ₂ , SO ₃ ...), hydrogen sulphide and other irritating gases.
Degradability	Not available.
Products of Degradation	Not available. Not available.
Corrosivity	No specific information is available in our database regarding the corrosivity of this product in presence of various materials.
Reactivity	Avoid contact with strong oxidizing agents. Keep away from heat, open flames, sparks and hot glowing surfaces.
Instability Temperature	Not available.
Conditions of Instability	No additional remark.

WHMIS 	Protective Clothing 	TDG Road / Rail
A B-5 D-1B		CONSUMER COMMODITY.



Section 6. Toxicological Properties

Routes of Entry	Ingestion. Inhalation.
TLV	<p>Methylene chloride TWA: 100 CEIL: 250 (ppm) TWA: 700 CEIL: 870 (mg/m³)</p> <p>Toluene TWA: 50 CEIL: 150 (ppm) TWA: 375 CEIL: 560 (mg/m³)</p> <p>Liquefied petroleum gas TWA: 1000 CEIL: 1250 (ppm) TWA: 1800 CEIL: 2250 (mg/m³)</p> <p>Consult local authorities for acceptable exposure limits.</p>
Toxicity to Animals	<p>WARNING: THE LC50 VALUES HEREUNDER ARE ESTIMATED ON THE BASIS OF A 4-HOUR EXPOSURE.</p> <p>Acute oral toxicity (LD50): 1987 mg/kg (Mouse) (Methylene chloride). Acute dermal toxicity (LD50): > 5000 mg/kg (Rabbit) (Toluene). Acute toxicity of the vapor (LC50): > 5000 ppm (Rat) (Toluene).</p>
Chronic Effects on Humans	Prolonged or repeated skin contact may lead to dermatitis.
Acute Effects on Humans	<p>EYE CONTACT: May cause moderate irritation, redness, tearing, blurred vision, conjunctivitis, corneal burns and possibly corneal damage.</p> <p>SKIN CONTACT: May cause irritation, defatting, drying and cracking of skin. Prolonged and repeated contact may lead to dermatitis.</p> <p>INHALATION: Vapours may be irritating to the nose, throat and respiratory tract. Excessive inhalation of vapours may cause Central Nervous System effects including dizziness, weakness, fatigue, nausea, headache and possible unconsciousness.</p> <p>INGESTION: May cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into the lungs may cause chemical pneumonitis, which can be fatal.</p> <p>Can be fatal if inhaled or ingested. This product may irritate eyes and skin upon contact.</p>
Synergetic Products (Toxicologically)	Not available.
Irritation/Corrosivity	Not available.
Sensitization	Not available.
Carcinogenic Effects	Not available.
Toxic Effects on Reproduction	Not available.
Teratogenic Effects	Not available.
Mutagenic Effects	Not available.

Section 7. Preventive Measures

Small Spill and Leak	Ventilate area and eliminate all sources of ignition. Keep away from heat. Absorb with an inert DRY material and place in an appropriate waste disposal container.
Personal Protective Equipment	Safety glasses and chemical resistant gloves. Be sure to use a MSHA/NIOSH approved respirator or equivalent when ventilation is inadequate.
Large Spill and Leak	Not applicable for aerosol containers.
Protective Clothing	Not applicable for aerosol containers.



WHMIS	Protective Clothing	TDG Road / Rail
		
A B-5 D-1B		CONSUMER COMMODITY.

Engineering Controls	Use under well-ventilated conditions.
Precautions	Contents under pressure. Container may explode if heated. Direct inhalation of spray may be harmful. Keep out of reach of children.
Storage	Store in a cool, dry place. Do not place in hot water or near radiators, stoves or other sources of heat. Do not puncture or incinerate container or store at temperatures over 50°C or in direct sunlight.
Handling	Do not use in the presence of open flame, sparks or ignition sources. Keep away from heat. Avoid breathing vapours or spray mists. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. After handling, always wash hands thoroughly with soap and water.
Waste Disposal	Recycle to process, if possible. Consult your local or regional authorities. Do not dispose in sewers. When container is empty, press button to release all pressure, then dispose of in garbage can.
Special Shipping Information	Not available.

Section 8. First Aid

Eye Contact	Flush eyes with plenty of running water for at least 15 minutes, lifting upper and lower lids, occasionally. Get medical attention.
Skin Contact	Wash thoroughly with soap and water. If irritation persists, get medical attention. Remove contaminated clothing and wash before reuse.
Hazardous Skin Contact	No additional information.
Slight Inhalation	Remove affected person to fresh air. If breathing is difficult, administer oxygen. If breathing stops give artificial respiration. Keep person warm, quiet and get medical attention.
Hazardous Inhalation	No additional information.
Slight Ingestion	If swallowed, call physician or poison control centre immediately. DO NOT induce vomiting. Rinse mouth with water. Aspiration of material into lungs due to vomiting may cause chemical pneumonitis which can be fatal.
Hazardous Ingestion	No additional information.

Section 9. MSDS Preparation

References	Not available.
No additional remark.	
Validated by Regulatory Affairs Dept. on 06/1/2010	

Emergency Phone: CANUTEC (24 HR) (613) 996 - 6666



Responsible Name/ Telephone No.	
--	--

Classification


TDG Road / Rail	CONSUMER COMMODITY.
------------------------	---------------------

TRIM ADHESIVE (STT)

Page Number: 5

WHMIS	Protective Clothing	TDG Road / Rail
		
A B-5 D-1B		CONSUMER COMMODITY.

Not applicable.

<p>WHMIS</p> <p>WHMIS CLASS A: Compressed gas. WHMIS CLASS B-5: Flammable aerosol. WHMIS CLASS D-1B: Material causing immediate and serious toxic effects (TOXIC).</p>	
--	---

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.