

MATERIAL SAFETY DATA SHEET

1. PRODUCT AND PREPARATION INFORMATION

Manufacturer: Dominion Sure Seal Group of Companies
6175 Danville Road, Mississauga, Ontario
Canada, L5T 2H7
(905)670-5411
U.S.A. 1-800-265-0790

Emergency telephone numbers: Dominion Sure Seal (8 AM TO 4 PM EST)
(905)670-5411
CANUTEC (24 HR)
(613) 996 – 6666

Product Name: SURE WIPE 18.9L
Product Stock: UUSW5
Product Code: 6005
Synonyms: Not Applicable
Chemical Family: Solvent
Molecular Formula: Mixture
Product Use: Multi-Purpose Solvent
Prepared by: Regulatory Department
Preparation Date: January 24, 2013

2. HAZARDOUS INGREDIENTS

Hazardous Ingredients	CAS Number	Wt. %	TLV	LD/50 mg/kg Route, Species	LC50; mg/m3 Route, Species
Light Aliphatic Solvent Naphtha (Petroleum)	64742-89-8	30 – 40	300 ppm	> 8 ml/kg (oral-rat) > 4 ml/kg (dermal-rat)	3400 ppm (rat, 4h)
Mineral Spirits	8052-41-3 or 64742-88-7	30 – 40	100 ppm	> 34.6 g/kg (oral-rat) 15.4 g/kg (dermal-rbt)	> 21,400 (rat, 4h)
Xylene (mixed isomers) *	1330-20-7	15 – 25	100 ppm	5,500; 7000 mg/kg (oral-rat) 12,270 mg/kg (dermal-rbt)	49,000 (rat,4h) 30,000 (mouse,2h) 19,900 (mouse,7h)
Acetone	67-64-1	5 – 15	500 ppm	5250 to 8400 (oral-various) >15,700 (dermal-rbt)	50,100 (rat,8h)

* Xylene is known to contain 18 – 20% by weight Ethylbenzene CAS # 100-41-4.

The other components of this product are not considered hazardous under applicable U.S. OSHA and/or Canadian WHMIS regulations.

2. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid
Appearance	Clear, colorless
Odour	Hydrocarbon
Odour Threshold	Not Available
Boiling Point (°C)	56 (Acetone)
Melting/Freezing Point (°C)	Not Available
Vapour Density (Air = 1)	> 1
Specific Gravity (Estimate)	0.792
Vapour Pressure (mm Hg)	24 kPa (Acetone)
Evaporation Rate, n-Butyl Acetate = 1	>1
pH	Not Applicable
Solubility in Water	Partially Miscible

4. FIRE AND EXPLOSION HAZARD

Flammability:	Yes
If Yes, Under Which Conditions:	Excessive heat, sparks and open flame.
Flammability Limits in Air (%):	2.5 – 12.8
Flash Point (CC °C)	> -18 (Acetone; CC)
Autoignition Temperature (°C):	Not Available
Hazardous Combustion Products:	Carbon monoxide, Unidentified organic compounds.
Sensitivity to Mechanical Impact:	Not available. Not expected to be sensitive to mechanical impact.
Rate of Burning:	Not available.
Explosive Power:	Not available.
Sensitivity to Static Discharge:	Not available. Expected to be sensitive to static discharge when vapours in air are between the flammability limits.
Extinguishing Media:	Carbon Dioxide, dry chemicals, foam, water fog. In case of a large fire cool containers with water jet in order to prevent pressure build up, autoignition or explosion.

5. REACTIVITY DATA

Chemical Stability:	Yes, under normal conditions.
Compatibility with Other Substances:	No, with strong oxidizing agents.
Hazardous Products of Decomposition:	Carbon monoxide, Unidentified organic compounds.
Hazardous Polymerisation:	Will not occur.

6. TOXICOLOGICAL PROPERTIES

Route of Entry:	
Skin Contact:	Yes
Skin Absorption:	Yes
Eye Contact:	Yes
Inhalation:	Yes
Ingestion:	Yes
Effects of Exposure:	Vapors may cause irritation of the eyes, nose and throat. Prolonged exposure to high vapor concentrations may be harmful and cause adverse effects including headache, nausea, dizziness, drowsiness, confusion and incoordination. Eye contact may cause irritation. Skin contact may cause irritation. Prolonged contact may cause defatting of the skin resulting in irritation, itching, dryness and cracking of the skin. Prolonged and repeated skin contact may lead to dermatitis. This product is only slightly toxic by ingestion. Ingestion of large amounts is likely to produce symptoms similar to those described for inhalation.
Carcinogenicity of material:	Ethylbenzene is listed by IARC as 2B – The chemical is possibly carcinogenic to humans.
Reproductive effects:	Animal tests show that xylene is a possible reproductive hazard – may cause fetotoxicity.
Teratogenicity:	No information is available and no adverse Teratogenic effects are anticipated.
Mutagenicity:	No information is available and no adverse Mutagenic effects are anticipated.
Sensitization of the material:	Material is not expected to be a skin or respiratory sensitizer.

7. PREVENTIVE MEASURES

Eye Protection:	Chemical safety glasses/goggles with side shields is the minimum requirement.
Skin Protection:	Wear chemical resistant gloves.
Respiratory Protection:	Wear a NIOSH/MSHA approved respirator if exposure exceeds occupational limits (see Section 2).
Engineering Controls:	Exhaust ventilation is recommended if used indoors on continuous basis.

Leak/Spill Clean-Up Procedures: Ventilate enclosed spaces. Collect product for disposal. Do not use combustible materials such as sawdust as an absorbent. Eliminate all sources of ignition. Notify applicable government authority if release is reportable or could adversely affect the environment.

Storage Instructions: Keep away from moisture, heat, sparks, and open flames.

8. FIRST AID MEASURES

Eye Contact:

In case of eye contact, immediately flush eyes with running water for a minimum of 15 minutes. Hold eyelids open during flushing. If irritation persists, repeat flushing. Obtain medical attention immediately.

Skin Contact:

For skin, wash thoroughly with soap and water. If irritation develops, get medical attention.

Inhalation:

If affected by inhalation of vapour or spray mist, move to fresh air. Get medical attention if breathing is difficult.

Ingestion:

If swallowed, do not induce vomiting. If vomiting occurs, keep head below hips to prevent aspiration into lungs. Rinse mouth with water. Drink 1-2 glasses of milk to dilute product. Water may be used instead but is not as effective. Never give anything by mouth to an unconscious person. Obtain medical attention immediately.

9. TRANSPORT INFORMATION

Proper Shipping Name:	Paint Related Material
UN Number:	1263
Class or Division:	3
Sub Risk:	Not Applicable
Packing Group:	II

10. REGULATORY INFORMATION

U.S. Federal Regulations

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 Hazard Category:

Irritant – skin & eye; Flammable; target organ effects reported.

Toxic Substances Control Act (TSCA): All components of this product are included on the TSCA inventory.

Comprehensive Environmental Response and Liability Act of 1980 (CERCLA) Hazardous Substances:

Chemical Name	CAS Number	Reportable Quantity (RQ)
Xylene (mixed isomers)	1330-20-7	100
Ethylbenzene	100-41-4	1000
Acetone	67-64-1	5000

CAA, Section 112 Hazardous Air Pollutants:

Chemical Name	CAS Number	Concentration
Xylene (mixed isomers)	1330-20-7	14 – 18 %
Ethylbenzene	100-41-4	3 – 5 %

Superfund Amendments and Reauthorization Act (SARA) Title III Information:

SARA (EPCRA) Section 311/312 (40 CFR 370) Hazard Categories:

- Immediate Hazard: Yes
- Delayed Hazard: Yes
- Fire Hazard: Yes
- Pressure Hazard: No
- Reactivity Hazard: No

This product contains the following extremely hazardous substance(s) subject to the reporting requirements of SARA (EPCRA) Section 302:

Chemical Name	CAS Number	Concentration
None	NA	NA

This product contains the following toxic chemical(s) subject to reporting requirements of SARA (EPCRA) Section 313 (40 CFR 372)

Chemical Name	CAS Number	Concentration
Xylene (mixed isomers)	1330-20-7	14 – 18 %
Ethylbenzene	100-41-4	3 – 5 %

State Regulations

California: This product contains the following chemicals(s) known to the State of California to cause cancer, birth defects or reproductive harm:

Component	CAS Number	Maximum %
Ethylbenzene	100-41-4	3 – 5 %

International Regulations

Canadian Workplace Hazardous Materials Information System (WHMIS):

B2, D2A, D2B

Canadian Environmental Protection Act (DSL): All of the components of this product are included on the Canadian Domestic Substances list (DSL).

European Inventory of Existing Chemicals (EINECS): All of the components of this product are included on EINECS.

11. OTHER INFORMATION

VOC Compliance Statement:

VOC Content – Less Exempts:	792 g/l (6.61 lb/gal)
VOC Content – Total Material:	713 g/l (5.95 lb/gal)
VOC Content – % by weight:	90 % max
Density:	0.792 g/ml
Volatiles Content:	100 % by weight max
Exempt Content:	10 % by weight (10 % by volume)

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR. **This MSDS is valid for three years.**

The information contained herein is based on data considered accurate. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Dominion Sure Seal assumes no responsibility for personal injury or property damage to vendees or users or third parties, caused by the material. Such vendees or users assume all risks with the use of the material.