

MATERIAL SAFETY DATA SHEET

1. PRODUCT AND PREPARATION INFORMATION

Manufacturer:	Dominion Sure Seal Group of Companies 6175 Danville Road, Mississauga, Ontario Canada, L5T 2H7 (905)670-5411 U.S.A. 1-800-265-0790
Emergency telephone numbers:	Dominion Sure Seal (8 AM TO 4 PM EST) (905)670-5411 CANUTEC (24 HR) (613) 996 – 6666
Product Name:	Large Panel Adhesive
Product Code:	XSM7002 Part B
Synonyms:	Not Applicable
Chemical Family:	Amidoamine
Molecular Formula:	Mixture
Product Use:	Epoxy Curing Agent
Prepared by:	Regulatory Department
Preparation Date:	June 1, 2014

2. HAZARDOUS INGREDIENTS

Hazardous Ingredients	CAS Number	Wt. %	TLV ppm	LD/50 Route, Species	LC/50 Route, Species
Amidoamine Resin	68443-08-3	30-60	Not Available	1.23 ml/Kg (ORL-RAT) 1.7 ml/Kg (DRMAL-RBT)	Not Available
Talc	14807-96-9	10-30	2 mg/M3	Not Available	Not Available
Calcium Metasilicate	13973-17-0	10-30	10 mg/M3	Not Available	Not Available

2. HAZARDOUS INGREDIENTS (CONTINUED)

Hazardous Ingredients	CAS Number	Wt. %	TLV ppm	LD/50 Route, Species	LC/50 Route, Species
Siloxanes and Silicones Reaction Products with Silica	67762-90-7	3-7	10 mg/M3	Not Available	Not Available
Diethylenetriamine	111-40-0	1-5	4.2 mg/M3	1080 mg/Kg (ORL-RAT) 1046 mg/Kg (DRMAL-RBT)	Not Available
Bisphenol A	80-05-7	1-5	Not Available	2,230 mg/Kg (ORL-RAT) 3,000 mg/Kg (DRMAL-RBT)	Not Available
Glass Beads	65997-17-3	1-5	10 mg/M3	Not Available	Not Available

INTENTIONALLY LEFT BLANK

3. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid
Appearance	Creamy
Odour	Slight Ammoniac
Odour Threshold	Not Available
Boiling Point (Deg.C)	Not Available
Melting/Freezing Point (Deg. C)	Not Available
Vapour Density (Air = 1)	> 1
Specific Gravity	1.4-1.5
Vapour Pressure (mm Hg)	Not Available
Evaporation Rate, n-Butyl Acetate = 1	< 1
PH	Alkali
Solubility in Water	Partial

4. FIRE AND EXPLOSION HAZARD

Flammability:	No.
If Yes, Under Which Conditions:	Not Applicable.
Flammability Limits in Air (%):	Not Available
Flash Point (TCC deg.C)	> 200 deg. C
Autoignition Temperature (Deg. C):	Not Available
Hazardous Combustion Products:	Carbon monoxide, Nitrogen oxides, Silica oxide.
Sensitivity to Mechanical Impact:	Not available. Not expected to be sensitive to mechanical impact.
Rate of Burning:	Not available.
Explosive Power:	Not available.
Sensitivity to Static Discharge:	Not available. Not expected to be sensitive to static discharge.
Extinguishing Media:	Use any media that is appropriate for the surrounding fire.

5. REACTIVITY DATA

Chemical Stability: Yes, under normal conditions.
Compatibility with Other Substances: No, with strong acids, strong oxidizing agents.
Hazardous Products of Decomposition: Carbon monoxide, Nitrogen oxides, Silica oxide, Phenolics.
Hazardous Polymerisation: Will not occur.

6. TOXICOLOGICAL PROPERTIES

Route of Entry:
 Skin Contact: Yes
 Skin Absorption: No
 Eye Contact: Yes
 Inhalation: Yes
 Ingestion: Yes
Effects of Exposure: Corrosive material! Inhalation may cause irritation of the respiratory tract. Product contact with skin may cause skin irritation and burns. Eye contact will cause severe eyes irritation and burns. Swallowing may cause burning of the mouth and stomach. Other possible effects are abdominal pain, nausea and diarrhea.
Carcinogenicity of material: No information is available and no adverse Carcinogenic effects are anticipated.
Reproductive effects: No information is available and no adverse Reproductive effects are anticipated..
Teratogenicity: No information is available and no adverse Teratogenic effects are anticipated.
Mutagenicity: No information is available and no adverse Mutagenic effects are anticipated.

7. PREVENTIVE MEASURES

Eye Protection: Chemical safety goggles with side shields.
Skin Protection: Impervious gloves.
Respiratory Protection: If exposure exceeds occupational limits wear a NIOSH approved air-purifying respirator with organic vapour cartridges for mists and vapours.

Engineering Controls:	General ventilation. Exhaust ventilation is recommended if used indoors on continuous basis.
Leak/Spill Clean-Up Procedures:	Ventilate enclosed spaces. Collect product for disposal. Notify applicable government authority if release is reportable or could adversely affect the environment.
Storage Instructions:	Keep away from heat, sparks, and open flames.

8. FIRST AID MEASURES

In case of eye contact, immediately flush eyes with running water for a minimum of 15 minutes. Hold eyelids open during flushing. If irritation persists, repeat flushing. Obtain medical attention IMMEDIATELY. For skin, wash thoroughly with soap and water. If irritation develops, get medical attention. If affected by inhalation of vapour or spray mist, move to fresh air. If swallowed, do not induce vomiting. Rinse the mouth. Drink 1-2 glasses of milk to dilute product. Water may be used instead but not as effective. Obtain medical attention IMMEDIATELY.

9. TRANSPORT INFORMATION

Proper Shipping Name:	Corrosive Liquids, Basic, Organic, N.O.S. (Amidoamine resin)
UN Number:	3267
Class or Division:	8
Sub Risk:	Not Applicable.
Packing Group:	III

10. REGULATORY INFORMATION

WHMIS Classification: E

11. OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR. **This MSDS is valid for three years.**

Signature of preparer: Product Regulatory

The information contained herein is based on data considered accurate. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Dominion Sure Seal assumes no responsibility for personal injury or property damage to vendees or users or third parties, caused by the material. Such vendees or users assume all risks with the use of the material.